

Clifton Cameras Product Specification

Canon RF 5.2mm F2.8L DUAL FISHEYE Lens Full Spec

OPTICAL FEATURES/SPECIFICATIONS	
Image size	Full Frame
35mm film equivalent focal length (mm)	-
Angle of view(horzntl, vertl, diagnl)	190°, 190°, 190°
Lens construction (elements/groups)	10/12
Special optics	2 x UD
Special features	Dual Fisheye with Baseline length of 60mm
No. of diaphragm blades	7
Minimum aperture	16
Closest focusing distance (m)	0.2
Maximum magnification (x)	0.03
Control Ring	No
Image stabilizer OIS (1)	-
Image stabilizer IBIS x OIS (1)	-
AF actuator	-
Coatings	Super Spectra, SWC
Fluorine	Front
PHYSICAL SPECIFICATIONS	
Dust/moisture resistance (3)	Rubber ring on lens mount
Exterior coating	-
Filter diameter (mm)	Rear-mounted gelatin filter (35x20mm)
Max. diameter x length (mm) (2)	(121.1 x 83.6) x 53.5
Weight (g)	350
ACCESSORIES	
Lens cap	Lens Cap 5.2 (center pinch type)
Lens hood	-
Lens case/pouch	LS1014
Rear cap	Lens Dust Cap RF
Extender Compatibility	Not Compatible
Other Accessories	Hexagon wrench



Footnote:

- 1 Tested under CIPA standards
- 2 Lens dimensions when in retracted state
- 3 Lenses with dust/moisture resistance are fitted with a rubber ring on the lens mount which may cause slight abrasion of the camera mount. This in no way effects either the lens or camera performance.