

Clifton Cameras Product Specification

Canon Speedlite EL-1 Full Spec

Power

Guide No. (ISO100).meters
60 (200mm)¹

Zoom

Zoom head
Auto/Manual

Focal length coverage
24-200mm

Coverage with wide panel
14mm

Auto zoom for sensor size
Yes

Flash modes

Auto exposure control
E-TTL II / E-TTL

High speed sync (FP)
Yes

Manual / output settings
Yes - 1/1 to 1/8192²

Manual steps
1/3-stops

Continuous shooting priority (CP) mode
Yes

Continuous flashes in a burst
Maximum at full power: Approx. 170³

Strobe / output settings
Yes - 1/4 - 1/8192 (1/128 for optical transmission)

Stroboscopic Frequency
1 - 500Hz (199Hz using optical receiver function)

Flash-related function

FE lock

Yes

FE memory

Yes

Flash Exposure Compensation

±3 stops

Flash Exposure Bracketing

±3 stops

Second-curtain flash sync

Yes⁴

Modelling flash

Yes

Modelling lamp

2 x LED

(duration, brightness and colour temperature user selectable)

Colour temperature info communication

Yes

Wireless flash

Transmitter

Yes

Transmission type

Optical / Radio

Transmitter range (Optical / Radio)

Indoors: 0.7-15m / 30m (approx.)⁵

Outdoors: 0.7-10m / 30m (approx.)⁶

Receiver

Yes

Max. number of Transmitters / Receivers

Optical: Unlimited / Unlimited

Radio: 15 / 15 (16 in total of any combination)

No of groups (Optical/Radio)

3 (A/B/C) / 5 (A/B/C/D/E)

No of channels (Optical/Radio)

4 / Auto, 15

Remote Shutter Release

Yes

Flash head movement

Up



45, 60, 75, 90, 120°

Down

7°

Left

60, 75, 90, 120, 150 and 180°

Right

60, 75, 90, 120, 150 and 180°

AF Assist

AF Assist Beam

Yes

Number of AF points supported

1 - 191

AF-assist beam type

Infra-red / Emitting small series of flashes

Power Source

Battery

1 x Rechargeable Lithium-ion Battery

Battery Level Indicator

Yes⁷ - 5 levels / percentage

Minimum recycling time

Approx. 0.1 - 0.9 sec^{8, 9}

No. of flashes (fully charge battery)

Approx. 335 (at full power) to 2345¹⁰

External power supply

Yes - optional Compact Battery Pack CP-E4N¹¹

Construction

Dust and water resistance

Yes

Active cooling

Yes - internal fan

Mounting foot material

Metal

Misc.

Custom Functions

14 (9 personal functions)



Flash settings from camera menus

Yes¹²

External flash exposure sensor

Yes

PC terminal

Yes

Accessories

Included

Battery Pack LP-EL

Battery Charger LC-E6E

Speedlites Case

Mini Stand

Bounce Adapter SBA-EL

Colour Filter SCF-ELOR1

Colour Filter SCF-ELOR2

Optional

Speedlite Transmitter ST-E3-RT (radio)

Speedlite Transmitter ST-E2 (optical)

EX series Speedlites with receiver function

Compact Battery Pack CP-E4N

Battery Magazine CPM-E4 (for use with CP-E4N)

Off-Camera Shoe Cord OC-E3

Dimensions & weight

Size (W x H x D), mm

84.4 x 149.0 x 136.4 mm

Weight, grams

572g (body only)

687g (body + battery)