

Clifton Cameras Product Specification

Canon Zoemini S2 Instant Camera Full Spec

INDICATORS

Bottom LED (Charging)	Red: Charging Green: Charging complete
Top LED (Status)	White On : Device is On and Standby White Blinking : Processing Smartsheet / Preparing Printing / Firmware Updating Red On : Device is too High Temperature Red Blinking : Cover Opened / Printer Error / No Paper / Paper Jam Red/White Looping : Low Battery, Very Low Battery White Blinking : Device is Booting Blue Blinking : Smartsheet Error Cyan On : Device is too Low Temperature Cyan Blinking : Printer Head Cooling Magenta On : Mass Storage

	Mode
	Magenta
	Blinking : SD
	Card Error
	Yellow/Magenta/Cyan/White Looping :
	Printer is
	Printing
Filter Selection LED	1) Black & White Filter
	2) Vivid Color
	Filter
White Border LED	ON : Yes
	OFF : No
Speaker (Status)	1) Power On
	2) Camera
	Focus Lock
	3) Camera
	Shutter
	4) Camera
	Error (fail to
	take photo)
	5) microSD
	Card Insert /
	Eject
	6) microSD
	Card Error
HARDWARE	
Recommend Operating, Charging & Storage Temperature (°C)	15 -32°C (59 -90°F)
Recommend Operating Humidity (RH)	40-55% RH
Operating Temperature (°C)	5 -40°C (41 -104°F)
Operating Humidity (RH)	<70%RH
Print Technology	ZINKTM
Printer Head Life	1000 pages (under 25°C)
Print Speed	Approximately 50 second (Motor Start & Stop, at room temperature 25°C)
Print Resolution	314 x 600 dpi
Borderless Printing	YES
White Border Printing	YES
Filter Printing	YES (Black & White / Vivid Color)
Supported Media Type	ZINKTMphoto paper
Maximum Paper Size	2.0" x 3.0"
Paper Capacity	Up to 10 sheets of Canon ZINKTMphoto paper + 1 SMART SHEETTM
Automatic Paper Sensor	YES
Single Still Photo Resolution	8MP
Single Still Photo Format	JPG
Focal Length (35mm film)	25.66mm



equivalent)

Zoom Fixed

Aperture f/2.2
Focusing Range Fixed (Range: 30cm~∞ _)_
Sensitivity Auto (ISO Range : 100 -1600)
Flash Light YES
Flash Light Range 0.5M -1.0M
Ring Light YES (8 LEDs)
Effective Ring Light Range 0.3M-0.6M
White Balance Auto
Exposure Adjustment Auto
Connectivity to External Bluetooth 5.0

Mobile Device

NFC

iOS (Need 3rd party NFC reader, only available to iPhone 7 or later)

Android (workable with models with NFC support and preloaded NFC reader)

Mobile Application Canon Mini Print

Connector for Charging and Micro USB

Data Transfer

Battery Built-in Rechargeable lithium polymer Battery, 700mAh

Battery Life Average 25 photo papers

Charging Speed

Approximately 120 minutes (From 0% to fully charged)

Control Panel 1. Power Button

2. Shutter Button

3. Filter Button (Black & White / Vivid Color)

4. Border Button (White Border/ Customized Border)

5. Slide Switch (Landscape without Flash / Portrait with Auto Flash / Selfie with Ring Light)

Memory Card Compatible YES, MicroSD Card, up to 256GB

CONSUMABLE

ZINKTMP Photo Paper ZINK photo paper pouch (10 sheets)

2" x 3" photo paper / Peel-and-sticky back

Storage Environment Temperature: 0 -25°C,
Humidity: 40-55% RH

BODY

Body Upper Case Material Plastic

Body Middle Case Material Plastic

Body Lower Case Material Plastic

No. of Rubber Foot -

Others -

OTHERS

Auto-power Off YES (3mins / 5mins / 10mins)
(Setting on APP)

Live View YES (on APP)



Self Timer	YES (OFF / 3sec / 5sec / 10sec) (Setting on APP)
Remote Shutter	YES (on APP)
Customized Camera Sound Indication	YES (Power ON / Power OFF / Shutter) (Setting on APP)
Border Customization	YES (Through Mini Print App)
Reset Button	YES
PRODUCT SPECIFICATIONS	
Power Source	Rechargeable lithium polymer (700mAh)
Display Window Size	N/A
Body Color	Rose Gold / Pearl White / Dark Teal
Body Size (W x H x D)	121 x 80.3 x 22.4 mm
Weight	188g (Tentative)