

## Clifton Cameras Product Specification

### Elinchrom THREE Off Camera Flash Kit Full Spec

ELIN071	
<b>Size (Single Head):</b>	25.3 x 16.5 x 10.5 cm
<b>Type:</b>	TTL Battery Flash Kit
<b>Weight (Single Head):</b>	1650 g
<b>Power Ws:</b>	261 Ws
<b>Power Range:</b>	7-261 Ws
<b>Power Range (f stops):</b>	6
<b>Flash mode:</b>	Manual / TTL / HSS (with Transmitter Pro)
<b>Recycling time s:</b>	0.08-1.2
<b>Colour Temp °K:</b>	5900 K Action / 5600 K HSS (±150 K)
<b>Best Flash Duration:</b>	Action: 1/8500s / Normal: 1/1550s (T0.1)
<b>Flashes from one charge at min. Power:</b>	LED Lamp Off: 11250 / LED Lamp on 100%: 9000
<b>Flashes from one charge at max. Power:</b>	LED Lamp Off: 525 / LED Lamp on 100%: 400
<b>Power Source:</b>	Lithium-Ion Built-in - 41.04Wh
<b>Voltage Stabilisation:</b>	Yes, +/- 0.5%
<b>Modelling Light:</b>	Dimmable 20w (120w equivalent) Bi-Colour LED, CRI 95, 3000 Lumen
<b>Triggering:</b>	Built-In Skyport (20 frequency channels, 4 Groups), Built-In Bluetooth
<b>Auto Power Dumping:</b>	Adjusts power settings automatically in real time
<b>Fan Cooled:</b>	Smart proactive cooling
<b>Input:</b>	USB-C
<b>Battery Charge Status:</b>	On the display if ON and side logo if OFF
<b>Charging Time (with 65W USB-C Wall Charger):</b>	60m. (80%) – 100m. (100%) in Fast charge / 80m. (80%) – 135m. (100%) in Slow charge
<b>Charging Time (with 18W 20000 mAh Power Bank):</b>	80m. (80%) – 135m. (100%) in Fast charge / 105m. (80%) – 180m. (100%) in Slow charge
<b>LED run time (LED only, min/max power):</b>	10 hours / 90 minutes
<b>Umbrella fitting (on tilt head):</b>	7 – 8 mm