



# Clifton Cameras Product Specification

## Godox V1Pro Round Head Flash with Battery Full Spec

Model	V1Pro C	V1Pro N	V1Pro S
Compatible Cameras	Canon EOS cameras (E-TTL II auto flash)	Nikon cameras (i-TTL auto flash)	Sony cameras (TTL auto flash)
Power(1/1 output)	76Ws		
Flash Coverage	28 to 105mm <hr/> <ul style="list-style-type: none"> <li>• Auto zoom (flash coverage is set automatically to match the lens focal length and imagesize)</li> </ul> <hr/> <ul style="list-style-type: none"> <li>• Manual zoom</li> </ul> <hr/> <ul style="list-style-type: none"> <li>• Swinging/tilting flash head (bounce flash): 0 to 330° horizontally and -7° to 120° vertically</li> </ul>		
Flash Duration	1/300 to 1/20000 seconds		
<b>Exposure Control</b>			
Exposure Control System	E-TTL II auto flash and manual flash	i-TTL auto flash and manual flash	TTL auto flash and manual flash
Flash Exposure	Manual, FEB: ±3 steps with 1/3 increment each step (Manual FEC and FEB can be combined)		
Flash Exposure Lock (FEL)	With <FEL> button or <^> button		
Sync Mode	High-speed sync (up to 1/8000 seconds), first- curtain sync, and second-curtain sync		
Multi Flash	Provided (up to 100 times, 199Hz)		
<b>Wireless Flash (Radio 2.4G Transmission)</b>			
Wireless Function	Transmitter, Receiver, Off		
Transmitter Unit Groups	A, B, C, D	M, A, B, C	M, A, B, C



Controllable Receiver A, B, C, D, E (E group can be controlled by X series flash trigger)

Transmission Range  
(approx.) 100m

Channels 32 (01~32)

ID OFF/01~99

Modeling Flash Fired with camera's depth-of-field preview button

**Auto Focus Assist Beam**

Effective Range (approx.)  
Center: 0.6~10m / 2.0~32.8 feet  
Periphery: 0.6~5m / 2.0~16.4 feet

**LED Modeling Lamp**

Power 2w

Color Temperature 3300K±200K

**Power Supply**

Built-in Lithium Battery 7.2V/2980mAh

Recycle Time Approx. 1.5 seconds. Green LED indicator will light up when the flash is ready.

Number of Flashes  
at 1/1 step Approx. 500