



Clifton Cameras Product Specification

Lexar Professional CFexpress Type B Card Full Spec

Form Factor

CFexpress™ Type B

Interface

PCIe Gen3x2

Speed

up to 1750MB/s read, up to 1000MB/s write¹

Operating Temperature

-10° C to 70° C (14°F to 158°F)

Storage Temperature

-25 °C to 85 °C (-13 °F to 185 °F)

Dimension (L x W x H)

29.60 x 38.50 x 3.80 mm / 1.16" x 1.51" x 0.14"

Weight

7.65 g / 0.016 lbs

Warranty

Limited lifetime warranty

¹ Up to 1750MB/s read transfer, write speeds lower. Speeds based on internal testing. Actual sustained speed may vary depending on host device.

² Compatible with firmware enabled CFexpress™ cameras

Warning: CFexpress Type B cards are only compatible with devices that support the CFexpress format. Highest transfer speed achieved only when used with an CFexpress Type-B reader, indicated by a boxed USB logo on the product. Contact your device manufacturer for details.

Product appearance, performance, software offerings, and packaging may vary depending on ship date and available inventory.

Actual usable memory capacity may vary. 1GB equals 1 billion bytes.

Limited lifetime warranty is limited to 10 years from purchase in Germany and regions not recognizing lifetime warranty.

Lexar is not liable for any loss of data or images.

