



Clifton Cameras Product Specification

OM System M.Zuiko Digital ED 150-600mm F5.0-6.3 IS Lens Full Spec

FOCAL LENGTH - 150-600 mm

35MM EQUIVALENT FOCAL LENGTH - 300-1200 mm

LENS CONSTRUCTION - 25 elements in 15 groups (4 Super ED lenses, 2 ED lenses, 6 HR lenses, 1 HD lens)

SPLASHPROOF TYPE / DUSTPROOF - IEC Standard publication 60529 IPX1 (applies when the lens is used with OMDS splashproof body) / dustproof construction

ANGLE OF VIEW - 8.2 degrees - 2.1 degrees

CLOSEST FOCUSING DISTANCE - Wide: 0.56 m / Tele: 2.8 m

MAXIMUM IMAGE MAGNIFICATION - Wide: 0.35x / Tele: 0.20x

35MM EQUIVALENT MAX. IMAGE MAGNIFICATION - Wide: 0.70x / Tele: 0.39x

MINIMUM FIELD SIZE - Wide: 49.4 × 37.1 mm / Tele: 88.6 × 66.6 mm

NUMBER OF BLADES - 9 (circular aperture diaphragm)

MAXIMUM APERTURE - Wide: F5.0 (f:150 mm) - Tele: F6.3 (f:600 mm)

MINIMUM APERTURE - F22

LENS IS MECHANISM - VCM

IS PERFORMANCE - 5-axis sync IS 7 steps*

* According to CIPA standards. When attached to OM-1, with yaw and pitch applied to camera, half-press IS set to Off, and focal length set to 150mm.

5-axis sync IS 6 steps*

* According to CIPA standards. When attached to OM-1, with yaw and pitch applied to camera, half-press IS set to Off, and focal length set to 600 mm.

Lens IS 6 steps*

*Focal length : 150 mm

Lens IS 5 steps*

*Focal length : 600 mm

FILTER SIZE - Diameter 95 mm

DIMENSIONS - Diameter 109.4 × 264.4 mm

WEIGHT - 2,065 g (without Lens Cap, Lens Rear Cap and Lens Hood)

BOX CONTENTS - LH-103 Lens Hood, LC-95 Lens Cap, LR-2 Lens Rear Cap, Lens Strap, Instruction Manual, Warranty Card



SEPARATELY AVAILBALE ACCESSORIES - Zuiko PRF-ZD95 PRO Protection Filter, LH-103 Lens Hood, LC-95 Lens Cap, LR-2 Lens Rear Cap, LSC-1642 Lens Case, CSS-P121 Lens Strap

LC-95 LENS CAP

DIMENSIONS - Diameter 98.5 x 9.8 mm

WEIGHT - 24.3 g

LH-103 LENS HOOD

DIMENSIONS - Diameter 120.0 x 84.6 mm

WEIGHT - 151.4 g