

Clifton Cameras Product Specification

Panasonic LUMIX S Lens S-R2060 Full Specifications

Lens Construction	11 elements in 9 groups (2 aspherical lenses, 3 ED lenses, 1 UHR lens)
Mount	L-Mount
Optical Image Stabilizer	No
Focal Length	f=20-60mm
Aperture Type	9 diaphragm blades / Circular aperture diaphragm
Maximum Aperture	F3.5 (Wide) - F5.6 (Tele)
Minimum Aperture	F22
Closest Focusing Distance	0.15m/0.49ft (at focal length 20-26mm) / 0.4m/1.31ft (at focal length 60mm)
Maximum Magnification	0.43x
Diagonal Angle of View	94°(Wide) - 40°(Tele)
Dust and Splash Resistant	Yes*
Recommended Operating Temperature	-10°C to 40°C (14°F to 104°F)
Filter Size	φ67mm
Max. Diameter	φ77.4mm / 3.05inch
Overall Length	Approx. 87.2mm / 3.43inch (from the tip of the lens to the base side of the lens mount)
Weight	Approx. 350g / 12.35oz (excluding lens cap, lens rear cap and lens hood)
Standard Accessories	Lens cap, Lens rear cap, Lens hood
NOTE	*Dust and Splash Resistant does not guarantee that damage will not occur if this lens is subjected to direct contact with dust and water.