

## Clifton Cameras Product Specification

### Panasonic Leica DG SUMMILUX 9mm f1.7 ASPH Micro Four Thirds Lens Full Spec

<b>LEICA DG SUMMILUX 9mm / F1.7 ASPH.</b>	
Lens Construction	12 elements in 9 groups (2 aspherical lenses, 2 ED lenses, 1 UHR lens)
Nano Surface Coating	-
Mount	Micro Four Thirds mount
Optical Image Stabilizer	-
Focal Length	f=9mm (35mm camera equivalent 18mm)
Aperture Type	7 diaphragm blades / Circular aperture diaphragm
Maximum Aperture	F1.7
Minimum Aperture	F16
Closest Focusing Distance	0.095m/0.31ft
Maximum Magnification	0.25x / 0.5x (35mm camera equivalent)
Diagonal Angle of View	100°
Dust and Splash Resistant	Yes*
Recommended Operating Temperature	-10°C to 40°C (14°F to 104°F)
Filter Size	φ55mm
Max. Diameter	Approx. φ60.8mm / 2.39inch
Overall Length	Approx. 52.0mm / 2.05inch (from the tip of the lens to the base side of the lens mount)
Weight	Approx. 130g / 0.29lb (excluding lens cap, lens rear cap and lens hood)
Standard Accessories	Lens cap, Lens rear cap, Lens hood
	*Dust and Splash Resistant does not guarantee that damage will not occur if this lens is subjected to direct contact with dust and water.