

Clifton Cameras Specifications Sheet

For the

Ricoh GR III Digital Camera - Limited Street Edition

Specifications		
Lens	Lens Construction	6 elements in 4 groups (2 aspherical lens elements)
	Focal Length, Aperture	18.3mm (Approx. 28mm in 35mm equivalent focal length), F2.8~F16
Image Capture Unit	Image Sensor	Type: Primary color filter CMOS. Size: 23.5mm x 15.6mm
	Effective Pixels	Approx. 24.24 megapixels
	Sensitivity (Standard output)	ISO100~102400: Auto (ISO Auto Lower/Upper Limit and Minimum Shutter Speed can be set), Manual:
	Image Stabilization	Sensor-shift shake reduction (SR)(3-axis)
	AA Filter Simulator	Moiré reduction using SR unit (Off, Low, High)
	Dust Removal	Image sensor cleaning using ultrasonic vibrations "DR II"
File Formats	Still Image	File Format: RAW (DNG) 14bit, JPEG (Exif 2.3), DCF2.0 compliant Color Space: sRGB、AdobeRGB Recorded Pixels: 【3:2】 L(24M:6000x4000), M(15M:4800x3200), S(7M:3360x2240), XS(2M:1920x1280) 【1:1】 L(16M:4000x4000), M(10M:3200x3200), S(5M:2240x2240), XS(1.6M:1280x1280)
	Movie	File Format: MPEG4 AVC/H.264 (MOV) Recorded Pixels: Full HD (1920x1080, 60p/30p/24p), Sound: Built-in stereo microphone Recording Time: Up to 25 minutes or 4GB; automatically stops recording if the internal temperature of the camera becomes high.
	Storage Medium	Internal Memory (Approx. 2GB), SD/SDHC/SDXC Memory Card (Conforms to UHS-I standards)
Focus	Type	Hybrid AF (Image plane phase-matching and Contrast detection)
	Focus Mode	Auto-area AF, Zone AF, Select AF, Pinpoint AF, Tracking AF, Continuous AF, MF, Snap, ∞

	Face Detection	ON, Use only in Auto-area, OFF
	Focus Range (From lens face)	Normal: Approx. 0.1m~∞, Macro Mode: Approx. 0.06m~0.12m
Exposure	Exposure Mode	Program AE, Aperture Priority AE, Shutter Priority AE, Manual Exposure
	Metering Mode	Multi-segment, Center-weighted, Spot, Highlight-weighted
	Shutter Speed	1/4000 sec. - 30 sec. (Limit by aperture setting F2.8: 1/2500 sec, F5.6 or greater: 1/4000 sec.) Timed Exposure (10sec. - 20min.), Bulb, Time
	EV Compensation	Still Image: ±5EV, 1/3EV steps, Movie: ±2EV, 1/3EV steps
	ND Filter (2EV)	AUTO, ON, OFF
White Balance		Auto White Balance, Multi Auto White Balance, Daylight, Shade, Cloudy, Fl. - Daylight Color, Fl. - Daylight White, Fl. - Cool White, Fl. - Warm White, Tungsten, CTE, Manual White Balance, Color Temperature
	Fine Adjustment	Adjustable ±14 steps on A-B axis or G-M axis
Drive Mode	Drive	Single Frame Shooting, Continuous Shooting, Bracketing, Multi-exposure, Interval Shooting, Interval Composite
	Self-timer	10 sec., 2 sec., OFF
Shooting Functions	Crop	35mm, 50mm, OFF
	Image Control	Standard, Vivid, Monotone, Soft Monotone, Hard Monotone, Hi-Contrast B&W, Positive Film, Bleach Bypass, Retro, HDR Tone, Custom1, Custom2 Adjust parameters: Saturation, Hue, High/Low Key Adjustment, Contrast, Contrast (Highlight), Contrast (Shadow), Sharpness, Shading, Clarity, Toning, Filter Effect, Grain Effect*, HDR Tone Level (Adjust parameter varies depending on the selected image setting) * This parameter can be applied by firmware ver. 1.20. Please download from here.
	Dynamic Range Correction	Highlight Correction, Shadow Correction
	Noise Reduction	Slow Shutter Speed Noise Reduction, High-ISO Noise Reduction
	Display	Display magnification (4x, 16x), Grid display (4x4 Grid, 3x3 Grid), Histogram, Bright area warning, Electronic Level
Playback Functions	Playback View	Single frame, Multi-image (20, 48 frames), Display magnification (up to 16x, 100% view and Quick Zoom view available), Histogram (Y

		histogram, RGB histogram), Grid display (3x3 Grid, 4x4 Grid), Bright area warning, Auto Image Rotation,
	Base Parameter Adjustment	Brightness, Saturation, Hue, Contrast, Sharpness
	RAW Development	Aspect Ratio, JPEG Recorded Pixels, Color Space, White Balance, Image Control, Peripheral Illumination Correction, Sensitivity, High-ISO Noise Reduction, Shadow Correction
	Edit	Resize, Cropping, Levels Adjustment, White Balance Adjustment, Color Moiré Correction, Movie Edit (Cut), Movie Edit (Divide)
LCD Monitor	Type	3.0 inch TFT color LCD (aspect ratio 3:2), Approx. 1037K dots, Wide viewing angle, Air-gapless tempered glass
	Touch Screen	Capacitive sensing method
	Adjustments	Brightness, Saturation, Blue/Amber, Green/Magenta, Outdoor View Setting: ±2 Steps
Wireless LAN	Standards	IEEE 802.11b/g/n (HT20) (Wireless LAN standard protocol)
	Frequency (Center Frequency)	2412MHz~2462MHz (1ch~11ch)
	Security	Authentication: WPA2, Encryption: AES
Bluetooth®	Standards	Bluetooth® v4.2 (Bluetooth Low Energy)
	Frequency (Center Frequency)	2402MHz~2480MHz (CH0~CH39)
Interfaces	USB Type-C™	Battery Recharge/Power Supply (Optional AC Adapter required), Data Transfer: MTP, Video output: DisplayPort over USB-C (DisplayPort Alternative Mode)
	Hotshoe	Compatible with P-TTL Auto Flash Flash Mode: Flash On, Flash On+Red-eye, Slow-speed Sync, Slow Sync+Red-eye Flash Exposure Compensation: -2.0 -+1.0
	Lens adapter pin	Available
Power Supply	Battery Type	Rechargeable Battery DB-110
	AC Adapter	AC Adapter Kit K-AC166(Optional)
	Battery Life	Number of recordable images: Approx. 200 images, * With a fully-charged Rechargeable Lithium-ion Battery under the temperature at 23°C. Tested in compliance with CIPA standard. Actual results may vary depending on the shooting condition.

		Playback time: Approx. 180 minutes * The playback time is a guide based on RICOH's measurement method . The actual number differs according to usage conditions.
Dimensions and Weight	Dimensions	Approx. 109.4(W)×61.9(H)×33.2(D)mm (excluding protrusions)
	Weight	Approx. 257g (Included dedicated battery and SD memory card), Approx. 227g (Body only)
Included Accessories		Rechargeable Battery DB-110, USB Power Adapter, Power Plug, USB Cable I-USB166, Handstrap
Language		English, French, Germany, Spanish, Portuguese, Italy, Dutch, Danish, Swedish, Finnish, Polish, Czech, Hungarian, Turkey, Greek, Russian, Thai, Korean, Simplified Chinese, Traditional Chinese, Japanese
Storage		
(shots)		
Mode	Format/Size	Aspect Ratio
Still image	RAW	3:2
		3:2
		3:2
		1:1
		1:1
		1:1
	RAW+	3:2
		3:2
		3:2
		1:1
		1:1
		1:1
	[L] (JPEG)	3:2
		1:1
	[M] (JPEG)	3:2
		1:1
	[S] (JPEG)	3:2
		1:1
	[XS]	3:2

	(JPEG)	1:1
* 35mm equivalent focal length		
(min:sec)		
Mode	Size	Aspect Ratio
		(16:9)
		(16:9)
Movie**	Full HD	(16:9)
** The maximum recording time per shooting is 25minutes or 4GB.		
Operating Environment		
It is confirmed that a USB connection can be established between the camera and the following OSs.		
Windows®	Windows®10(F CU, CU) (32-bit, 64-bit), Windows® 8.1(32-bit, 64bit), Windows® 8(32-bit, 64-bit), or	

	Windows® 7(32-bit, 64-bit)	
Mac	macOS 10.14 Mojave, macOS 10.13 High Sierra, macOS 10.12 Sierra, OS X 10.11 El Capitan, OS X 10.10 Yosemite	