



# Clifton Cameras Product Specification

Canon RF 15-30mm F4.5-6.3 IS STM

## Optical Features/ Specifications

Image size: Full Frame

Angle of view: 100° 25' – 61° 55'

77° 20' - 43° 35'

110° 30' – 71° 35'

Lens construction (elements/groups): 13/11

Special optics: 1x PMo Aspherical, 2xUD

Special features: -

No. of diaphragm blades: 7

Minimum aperture: 22-32

Closest focusing distance (m): 0.28 (at 15mm) (Manual Focus: 0.128)

0.28 (at 20mm) (Manual Focus: 0.28)

0.28 (at 30mm) (Manual Focus: 0.28)

Maximum magnification (x): 0.09 (at 15mm) (Manual Focus: 0.52)

0.11 (at 20mm) (Manual Focus: 0.11)

0.16 (at 30mm) (Manual Focus: 0.16)

Control Ring: Via Focus Ring

Image stabilizer OIS: 5.5

Image stabilizer IBIS x OIS: 7

AF actuator: STM

Coatings: Super Spectra

Fluorine: No

## Physical Specifications

Dust/ moisture resistance: No

Exterior coating: -

Filter diameter (mm): 67



Max, diameter x length (mm): 76.6 x 88.4

Weight (g): 390

#### Accessories

Lens Cap: E-67 II (included)

Rear End Cap: Lens Dust Cap RF (included)

Lens Hood: EW-73E (sold separately)

Lens Case/ Pouch: LP1116 (sold separately)

Extender Compatibility: Not Compatible