

# Clifton Cameras Product Specification

## Canon RF-S 10-18mm F4.5-6.3 IS STM Lens

### Specifications

#### OPTICAL FEATURES / SPECIFICATIONS

|   |  |
|---|--|
| Image Size APS-C:                       | 35mm film equivalent focal                                 |
| length (mm):                            | 16-29mm  |
| Angle of view (horzntl, vertl, diagnl): | 97°10' - 64°30',<br>74°10' - 45° 30' ,<br>107°30' - 74°20' |
| Lens construction (elements/groups):    | 12 / 10  |
| Special optics:                         | 1 x PMo Aspherical   |
| Special features:                       | -  |
| No. of diaphragm blades:                | 7  |
| Minimum aperture:                       | 22 - 32  |
| Closest focusing distance (m):          | 0.14m (at 10-18mm)<br>(MF: 0.086m)                         |
| Maximum magnification (x):              | AF: 0.23x<br>MF: 0.5x                                      |
| Control Ring:                           | Combined / focus   |
| Image stabiliser OIS:                   | 4  |
| Image stabiliser IBIS x OIS:            | 6  |
| AF actuator:                            | STM  |
| Coatings:                               | Super Spectra  |
| Fluorine:                               | No   |

#### PHYSICAL SPECIFICATIONS

|                           |    |
|---------------------------|----|
| Dust/moisture resistance: | No |
| Exterior coating:         | -  |



Filter diameter (mm): 49

Max. diameter x length (mm): 69 x 44.9

Weight (g): 150

**ACCESSORIES**

Lens cap: E-49

Lens hood: EW-53B

Lens case/pouch: LP814

Rear cap: Lens Dust Cap RF

Extender Compatibility: Not compatible

Other Accessories: 49mm filters