



Clifton Cameras Product Specification

Canon Zoemini 2 Printer

INDICATORS Rear LED (Charging)

- Red: Charging
- Green: Charging completed
- Green flashing: Booting device
- Red/Green Looping : Charging

Fault Front LED (Status)

- White On : Device is On and Standby
- White Flashing : Booting Device / Standby without Bluetooth connection
- White with breathing effect : Preparing Printing / Firmware Updating
- Red On : Device is too High Temperature
- Red Flashing : Cover Opened / Printer Error / No Paper / Paper Jam Red/
- White Looping : Low Battery
- Blue Flashing: non-Canon Smartsheet
- Cyan On : Device is too Low Temperature
- Cyan with breathing effect: Printer Head Cooling
- Yellow/Magenta/Cyan/White Looping with breathing effect : Processing Smartsheet /Printer is Printing (Default Setting)

HARDWARE

Recommend Printing Temperature (°C): 15 - 32°C (59 - 90°F)

Recommend Printing Humidity (RH): 40-55% RH

Operating Temperature (°C) 5 - 40°C (41 - 104°F)

Operating Humidity (RH) <70% RH

Print Technology ZINK®

Printer Head Life 1000 pages (under 25°C)

Print Speed Approximately 50 second (Motor Start & Stop, at room temperature 25°C)

Print Resolution 313 x 500 dpi

Borderless Printing YES

Supported Media Type Canon ZINK® Photo Paper, Canon ZINK® Pre-Cut Sticker

Paper Size 2.0" x 3.0"

Paper Capacity Up to 10 sheets of Canon ZINK® photo paper + 1 SmartSheet®

Sensor YES (for Paper Detection/Paper Cover Detection)

Connectivity to External Mobile Device Bluetooth® 5.0

Mobile Application Canon Mini Print

Connector for Charging USB Type-C



Battery Built-in Rechargeable lithium polymer Battery, 500mAh (0V Charging Support)*

Battery Life Average 20 photo papers

Charging Speed

- Approximately 50 minutes (From 0% to fully charged)
- Approximately 36 minutes (From 0% to 80%)
- Approximately 20 minutes (From 0% to 50%)

* Its fast charging speed requires the USB Adaptors supports QC, PD or 5V@2.4A under temperature 10C - 40C condition. For other USB Adaptors such as 5V@1.5A or lower, it may not support fast charge

Control Panel 1. Power Button

CONSUMABLE / ACCESSORIES

Canon ZINK® Photo Paper Canon ZINK® Photo Paper (10 sheets per pouch) 2" x 3" photo paper size / Peel-and-sticky back

Canon ZINK® Pre-Cut Sticker

(Bundle Set Only)

Canon ZINK® Pre-Cut Sticker (10 sheets per pouch) 2" x 3" photo paper size / 1.3" sticker size /Peel-and-sticky back

Pouch case Set B: Printer pouch case x 1

Storage Environment Temperature: 0 - 25°C, Humidity: 40-55% RH

BODY

Body Upper Case Material Plastic

Body Middle Case Material Plastic

Body Lower Case Material Plastic

Top Plate Material Plastic

No. of Rubber Foot -

Others -

OTHERS

Auto-power Off YES (3mins / 5mins / 10mins) (Setting on APP)

Reset Button YES

PRODUCT STORAGE

CONDITION

Warehouse Storage

Environment (Sales Company

+ Sales Channel)

Temperature: 0 - 25°C, Humidity: 40-55% RH

Warehouse Storage Time

(Sales Company + Sales

Channel)

~ 1 Year (TBC)



PRODUCT SPECIFICATIONS

Power Source Rechargeable lithium polymer (500mAh)

Display Window Size N/A

Body Colour Rose Gold and White / White and Silver / Navy and

White

Body Size (W x H x D) 120 x 84 x 21.5mm

Weight 177g