



Clifton Cameras Product Specification

Canon RF 400mm F2.8L IS USM Lens Full Spec

Image size	Full Frame
Angle of view (horzntl, vertl, diagnl)	5°10', 3°30', 6°10'
Lens construction (elements/groups)	17/13
Special optics	2x Fluorite, 1X SUD
No. of diaphragm blades	9
Minimum aperture	32
Closest focussing distance (m)	2.5
Maximum magnification (x)	0.17
Control ring	No
Image stabilizer OIS	5.5
Image stabilizer IBIS x OIS	5.5
AF actuator	Ring USM
Coatings	ASC, Super Spectra
Fluorine	Front / Rear
PHYSICAL SPECIFICATIONS	
Dust/moisture resistance	Yes
Exterior coating	Heat Shield
Filter diameter (mm)	52 Drop in
Max. diameter x length (mm)	163 x 367
Weight (g)	2890

ACCESSORIES	
Lens Cap	E-180E
Lens hood	ET-155(WIII)
Lens case/pouch	Lens Soft case LS400
Rear Cap	Lens Dust Cap RF



Extender Compatibility	Compatible with RF 1.4x & RF 2x Extenders only
Other Accessories	Canon drop-in 52mm filters Canon Drop-In Circular Polarizing Filter 52 (WIII) Canon Lens Short Hood ET-1 55B
SPECIFICATIONS 1.4X EXTENDER	
Focal Length	560
Maximum Aperture	4-45
Maximum Magnification	0.25
AF Possible	Yes
IS	Yes
SPECIFICATIONS 2X EXTENDER	
Focal Length	800
Maximum Aperture	5.6-64
Maximum Magnification	0.36
AF Possible	yes
IS	yes