



## Clifton Cameras Product Specification

### Elinchrom ONE Full Spec

#### Overview

Flash output

131 Ws

Flash modes

Standard, HSS, TTL

Number of flashes

725 at full power

Weight

1.5 kg (3.3 lbs)

Energy

131 Ws/J

F-Stop

1m, 100 ISO, HP Reflector 26 cm, max power  
42.5

F-Stop

1m, 100 ISO, OCF Diffusion Dome, max power  
11.9

Power range

5 F-Stop / 7 – 131 Ws

Power increments

Manual / TTL

0.1 F-Stop / 0.3 F-Stop

Power range display

Elinchrom scale / 10 scale

0.1 – 4.3 (Elinchrom scale) / 5.8 – 10 (10 scale)

Best flash duration

t0.1 min/max power (Normal mode)

1/1530s – 1/155s

Best flash duration

t0.1 min/max power (Action mode)

1/7000s – 1/625s



Recycling time  
min/max power  
0.06s / 0.9s

Flash mode  
Manual / TTL / HSS (with Transmitter Pro)

Charging time  
with 18W 20000 mAh Power Bank  
80 m (80%) – 135 m (100%) / Fast charge (unit is ON)  
105 m (80%) – 180 m (100%) / Slow charge (unit is OFF)

LED modeling lamp  
LED modes  
ON/OFF, free, proportional, VFC

LED power  
20W / equivalent to 120W / 3000 lm / CRI 95

LED color temperature  
Presets from 2700 K to 6500 K

LED run time  
LED only, min/max power  
10 hours / 90 minutes

Skyport  
built-in  
20 frequency channels, 4 Groups

Skyport distance range  
Transmitter Pro, manual mode  
Indoor: up to 60 m / Outdoor: up to 200 m

Bluetooth  
built-in  
Version 4.2 / Compatible Studio Software Win, macOS, iOS

Dimensions  
without Diffusion Dome and tilt head  
22.5 x 10 x 10 cm  
8.5 x 3.9 x 3.9 inches

Weight  
with/without tilt head  
1.5 kg – 3.3 lbs / 1.3 kg – 2.9 lbs