



Clifton Cameras Product Specification

Panasonic LUMIX S 24mm F1.8 Full Spec

| | |
|-----------------------------------|---|
| LUMIX S 50mm F1.8 | |
| Lens Construction | 12 elements in 11 groups (3 aspherical lenses, 1 UED lens, 3 ED lens) |
| Mount | L-Mount |
| Optical Image Stabilizer | No |
| Focal Length | f=24mm |
| Aperture Type | 9 diaphragm blades / Circular aperture diaphragm |
| Maximum Aperture | F1.8 |
| Minimum Aperture | F16 |
| Closest Focusing Distance | 0.24m/0.79ft |
| Maximum Magnification | 0.15x |
| Diagonal Angle of View | 84° |
| Dust and Splash Resistant | Yes* |
| Recommended Operating Temperature | -10°C to 40°C (14°F to 104°F) |
| Filter Size | φ67mm |
| Max. Diameter | φ73.6mm / 2.90inch |
| Overall Length | Approx. 82.0mm / 3.23inch (from the tip of the lens to the base side of the lens mount) |
| Weight | Approx. 310g / 0.68lb (excluding lens cap, lens rear cap and lens hood) |
| Standard Accessories | Lens cap, Lens rear cap, Lens hood |
| | *Dust and Splash Resistant does not guarantee that damage will not occur if this lens is subjected to direct contact with dust and water. |