



# Clifton Cameras Product Specification

## DJI RS 3 Mini

### Specifications

Accessory Port:	1/4"- 20 Mounting Hole RSS Camera Control Port (USB-C) NATO Expansion Port
Battery:	Model: HB7-2450mAh-7.2V Type: 18650 Li-ion 2S Capacity: 2450 mAh Energy: 17.64 Wh Operating Time: 10 hours Charging Specification: 5 V/2 A Charging Time: Approx. 2.5 hours Suggested Charging Temperature: 5° to 40° C (41° to 104° F)
Connections:	Bluetooth 5.1 USB-C Charging Port
Ronin App Requirements:	iOS 11.0 or above Android 7.0 or above
Languages Supported by the Touchscreen:	English, Simplified Chinese, Traditional Chinese, German, French, Korean, Japanese, Spanish, Portuguese (Brazil), Russian, Thai
Tested Payload:	0.4-2 kg (0.8-4.4 lbs)
Maximum Controlled Rotation Speed:	Pan: 360°/s Tilt: 360°/s Roll: 360°/s
Mechanical Range:	Pan Axis: 360° continuous rotation Roll Axis: -95° to +240° Tilt Axis: -10° to +210°



cliftoncameras

Operating Frequency:	2.4000-2.4835 GHz
Bluetooth Transmitter Power:	<4 dBm
Operating Temperature:	-10° to 45° C (14° to 113° F)
Weight	Gimbal: 795 g (1.75 lbs) in portrait mode and 850 g (1.8 lbs) in horizontal shooting mode (both including the Quick-Release Plate and excluding the Extended Grip/Tripod)  Extended Grip/Tripod: Approx. 128 g (0.2 lbs)
Dimensions:	Folded: 323x195x98 mm (LxWxH, height excludes the Extended Grip/Tripod)  Unfolded: 180x159x296 mm (LxWxH, excluding camera and the Extended Grip/Tripod)
Included Accessories:	DJI RS 3 Mini Gimbal; USB-C Charging Cable (40cm); L-Shaped Multi-Camera Control Cable (USB-C, 30cm); RS Mini Quick-Release Plate; RS Mini Tripod; Screw Kit (D-Ring Camera Mounting Screw 1/4"-20 x 1, Screw 1/4"-20 x 1)