

## DJI RS 4 Mini Specification

### DJI RS 4 Mini

#### Specifications

Accessory Port	NATO Port  1/4"-20 Mounting Hole  RSS Camera Control Port (USB-C)  Pogo Pin (compatible with the DJI RS Intelligent Tracking Module)
Battery	Model: BHX724-3100-7.2
Type:	LiPo 2S
Capacity:	3100 mAh
Energy:	22.32 Wh
Max Runtime:	13 hours (stationary)*
Charging Specification:	9 V/2.5 A
Charging Time:	Approx. 1 hour and 50 minutes**
Suggested Charging Temperature:	5° to 40° C (41° to 104° F)

\*Measured with the equipment in a level and stationary state and the gimbal balanced. When the gimbal is in motion, the operating time will be reduced.

\*\*Tested in a 25° C (77° F) environment while using a 30W charger.

Connections	Bluetooth 5.1  USB-C Charging Port
Ronin App Requirements	iOS 14.0 or above  Android 9.0 or above
Languages Supported by the Touchscreen	English, Simplified Chinese, Traditional Chinese, German, French, Korean, Japanese, Spanish, Portuguese (Brazil), Russian, Thai
Tested Payload	0.4-2 kg (0.88-4.4 lbs)
Maximum Controlled Rotation Speed	Pan: 360°/s
Tilt:	360°/s



Roll:	360°/s
Mechanical Range	Pan Axis: 360° continuous rotation
Roll Axis:	-95° to +235°
Tilt Axis:	-110° to +210°
Axis Locks	Auto
Vertical Shooting	Supported
Operating Frequency	2.4000-2.4835 GHz
Bluetooth Transmitter Power	< 4 dBm
Operating Temperature	-10° to 45° C (14° to 113° F)
Weight	Gimbal: Approx. 890 g (1.96 lbs) (including the Quick-Release Plate and excluding the tripod)
Extended Grip/Tripod:	Approx. 140 g (0.3 lbs)
Dimensions	Folded: 236×64×316 mm (L×W×H, excluding the tripod and the Quick-Release Plate)
Unfolded:	175×182×338 mm (L×W×H, excluding camera, tripod, and the Quick-Release Plate)