

Clifton Cameras Product Specification

Fujifilm Instax Mini 90

Specifications

Film

Film	Fujifilm Instant Colour Film “instax mini” (separately available)
Film Size	86mm x 54mm
Picture Size	62mm x 46mm
Film Developing Time	Approximately 90 seconds (Varies depending on the ambient temperature)

Viewfinder

Viewfinder	Real image finder, 0.37x, with target spot and parallax adjustment for macro mode
-------------------	---

Lens

Lens	Move in / out type lens, 2 components, 2 elements, f=60mm, F=12.7
Focusing	Motor-driven 3-range switching, 0.3m – ∞ (macro mode: 0.3m – 0.6m, normal mode: 0.6m – 3.0m, landscape mode: 3.0m – ∞)

Exposure

Shutter Speed	Programmed electronic shutter release, 1.8 – 1/400 sec. shutter speeds (macro mode: aperture automatically fixed at F22, bulb mode: maximum 10-second shutter open time)
Exposure Control	Automatic, LV5.0 – 15.5 (ISO800), lighten-darken control $\pm 2/3EV$, +1EV

Other

Flash	Automatic electronic flash (with brightness adjustment function), forced firing mode (with brightness adjustment function), flash off mode, red eye reduction mode
Self-timer	Electronically controlled, approx. 10 second delay, Continuous shooting mode can be stopped mid-run
LCD Screen	Liquid Crystal – Exposure counter (number of remaining shots), Macro mode, Brightness control, Self timer, Flash ON / OFF, Mode button(Party / Kids / Landscape / Double exposure / Bulb)
Battery	Power Supply – NP-45A lithium-ion rechargeable battery. Charge capacity: 10 film packs (based on our test conditions)
Dimensions	113.4mm x 91.9mm x 57.2mm, 296g (excluding the battery, strap and film)



Accessories

Rechargeable Li-ion battery (NP-45S)

Shoulder strap

Battery charger

Instruction manual