

Clifton Cameras Product Specification

Fujifilm instax mini Evo

Specifications

Camera Function

Image sensor	1/5-inch CMOS with primary color filter
Number of recorded pixels	2560 x 1920
Storage media	Internal memory, microSD/microSDHC memory card
Storage capacity	Approximately 45 images in internal memory, approximately 850 images per 1 GB in microSD/microSDHC memory card
Recording method	DCF compliant Exif Ver 2.3
Focus distance	f = 28 mm (35-mm film equivalent)
Aperture	F2.0
Auto focus	Single AF (with AF Illuminator)
Shooting distance	10 cm to ∞
Shutter speed	1/4 second to 1/8000 second (automatic switching)
Shooting sensitivity	ISO100 to 1600 (automatic switching)
Exposure control	Program AE
Exposure compensation	-2.0 EV to +2.0 EV (1/3 EV step)
Metering method	TTL 256 split metering, multi metering
White balance	Auto, Fine, Shade, Fluorescent 1, Fluorescent 2, Fluorescent 3, Incandescent
Flash	Auto flash / Forced flash / Suppressed flash Shooting range with flash: Approximately 50 cm to 1.5 m
Self-timer	Approximately 2 seconds / approximately 10 seconds
Image effects	10 lens effects, 10 film effects Total of 100 effects by multiplying above

Print Function

Exposure Print pixel count	1600 x 600 dots (800 x 600 dots when printed from smartphone app)
Exposure resolution	25 dots / mm x 12.5 dots/ mm (635 x 318 dpi, 40 x 80 µm dot pitch) 12.5 dots / mm when printed from smartphone app (318 dpi, 80 µm dot pitch)
Interface	Standard compliance: Bluetooth Ver. 4.2 (BLE)
Exposure gradation	RGB gradation of 256 colors
Printable image format	JPEG images taken with this unit
Print output time	Approximately 16 seconds * Plus 7 seconds when printed using instax-Rich Mode immediately after startup.
Print function	Images in the internal memory and images in the memory card can be printed
Reprint	Reprint is possible for images stored in print history (up to 50)

Other

Smartphone app linked functions	Smartphone image print function, remote shooting function, printed image transfer function, firmware upgrade function
LCD screen	3.0-inch TFT color LCD screen Pixel count: Approximately 460,000 dots
External interface	Micro USB Micro-B (for charging only)
Power supply	Lithium ion battery (internal type: not removable)
Charging function	Built-in
Possible number of printed images	Approximately 100 (from full charge) * The number of prints depends on the usage conditions.
Charging time	Approximately 2 to 3 hours * Charging time depends on the temperature.
Main unit dimensions	87 mm x 122.9 mm x 36 mm (excluding projecting parts)
Main unit weight	Approximately 285 g
Operating environment	Temperature: 5°C to 40°C Humidity: 20% to 80% (no condensation)



Film used FUJIFILM instant film "instax mini" (sold separately)

Included Accessories Shoulder strap, USB cable for charging, User guide