



## Clifton Cameras Product Specification

### LUMIX S 35mm F1.8 Full Spec

**Lens Construction:** 11 elements in 9 groups (3 aspherical lenses, 3 ED lenses)

**Mount:** L-Mount

**Optical image Stabilizer:** No

**Focal Length:**  $f = 35\text{mm}$

**Aperture Type:** 9 diaphragm blades / Circular aperture diaphragm

**Maximum Aperture:** F1.8

**Minimum Aperture:** F22

**Closest Focusing Distance:** 0.24m/0.79ft

**Maximum Magnification:** 0.22x

**Diagonal Angle of View:** 63°

**Dust and Splash Resistant:** Yes\*

**Recommended Operating Temperature:** -10°C to 40°C (14°F to 104°F)

**Filter Size:**  $\phi 67\text{mm}$

**Max, Diameter:**  $\phi 73.6\text{mm}$  / 2.90inch

**Overall Length:** Approx. 82.0mm / 3.23inch (from the tip of the lens to the base side of the lens mount)

**Weight:** Approx. 295g / 0.65lb (excluding lens cap, lens rear cap and lens hood)

**Standard Accessories:** Lens cap, Lens rear cap, Lens hood

\*Dust and Splash Resistant does not guarantee that damage will not occur if this lens is subjected to direct contact with dust and water.