



Clifton Cameras Product Specification

Olympus M.Zuiko Digital ED 8-25mm F4.0 PRO Lens

Specifications

Focal Length	8-25mm
35mm Equivalent Focal Length	16-50mm
Lens Construction	16 elements in 10 groups: (1 DSA lens, 2 Aspherical ED lenses, 1 Super ED lens, 1 ED lens, 1 Super HR lens, 1 HR lens, 1 HD lens)
Splashproof Type / Dustproof	IEC Standard publication 60529 IPX1 / Dustproof construction
Focusing System	High-speed Imager AF (MSC) Linear Motor Drive System
Angle of View	107 degrees - 47 degrees
Closest Focusing Distance	0.23 m (throughout the zoom range)
Maximum Image Magnification	Wide: 0.07x / Tele: 0.21x
35mm Equivalent Max. Image Magnification	Wide: 0.14x / Tele: 0.42x
Minimum Field Size	Wide: 241.9 x 181.8 mm / Tele: 83.0 x 62.4 mm
Number of Blades	7 (circular aperture diaphragm)
Maximum Aperture	F4.0
Minimum Aperture	F22
Filter Size	Diameter 72 mm
Dimensions	Diameter 77 x 88.5 mm
Weight	411 g (without lens cap, lens rear cap and lens hood)
Box Contents	LC-72C Lens Cap, LR-2 Lens Rear Cap, LH-76E Lens Hood, CS-53 Wrapping Cloth, Instruction Manual, Olympus Local Warranty Card
Optional Accessories	PRF-ZD72 PRO Protection Filter LSC-0914 Lens Case