



Clifton Cameras Product Specification

Rode Wireless GO II

Acoustic & Electrical Specifications

Acoustic Principle: Pre-polarised pressure transducer

Polar Pattern: Omnidirectional

Frequency Response: 50Hz – 20kHz

Maximum SPL (Mic): 100 dB SPL (1KHz @ 1m) dBu

Maximum Input Level (3.5mm): -20 dBV

Microphone Preamp Gain: 20 dB

Equivalent Noise Level (A-weighted): 22 dBA

Power Requirements: In-built rechargeable lithium-ion battery charged via USB 5V, 0.3A

Operating Time: Up to 7 hours

Analog Inputs: 3.5mm TRS (lavalier microphone input)

Analog Outputs: 3.5mm TRS

Transmission Range: 200m (line of sight)

Computer Connectivity: USB Type-C

Operating System Requirements: macOS 10.11 above or Windows 10 and above

Mechanical Specifications

Weight (grams):

- TX: 30g
- RX: 32g

Dimensions (Millimetres):

- TX: Length: 44, Width 45.3, Height 18.3
- RX: Length: 44, Width 45.5, Height 18.3

Included Accessories:

- 2 x Fur Windshields
- 2 x USB-C Cables
- 1 x SC5 3.5mm TRS Cable
- 1 x Carry Pouch