



# Rode Wireless ME Dual Specification

## Rode Wireless ME Dual

### Specifications

Acoustic Principle:	Pre-polarised pressure transducer
Polar Pattern:	Omnidirectional
Frequency Range:	20 Hz – 20 kHz
Dynamic Range:	100dB
Max SPL:	122dB SPL
Equivalent Noise (dBA):	22dBA
Analog Inputs:	TRS (lavalier microphone Input)
Output Connection:	3.5mm TRS USB-C
Computer Connectivity:	USB-C
Bit Depth:	24-bit
Sample Rate:	48 kHz
Minimum Operating Systems Requirements:	macOS 10.15 above Windows 10 and above iOS 14 Android 11
Power Requirements:	In-built rechargeable lithium-ion battery charged via 5V USB
Operating Time:	7 hours
Transmission Range:	>100m (line of sight)
Weight (grams):	TX 32 RX 32
Dimensions (millimetres):	TX: 44mm x 45.3mm x 18.3mm RX: 44mm x 45.3mm x 18.3mm
Included Accessories:	2 x Transmitters



1 x Receiver

1 x SC21 USB-C to Lightning Cable

2 x SC22 USB-C to USB-C Cable

1 x SC2 3.5mm TRS to TRS cable

1 x SC7 3.5mm TRRS to TRS cable

3 x Fur windshield

1 x Carry Pouch